# **Spaceball XL - Product Specification**



## Univers – Classics among rope playground equipment

Net structures offer hours of fun and adventure on several levels – climbing and swinging, up and down, horizontally and vertically – space on earth.

The original spatial nets: Born over 40 years ago as a play concept, continuously further developed in form and detail, still popular even after several generations.

### Spaceball XL - at a glance.

**Product Family:** Univers Item Number: 90.100.601 Children's Age: Fall Height (DIN EN 1176): 2.47m (8'-2") Length x Width x Height:  $7.2 \text{ m} \times 7.2 \text{ m} \times 6.0 \text{ m}$ (23'-5" x 23'-5" x 19'-9")

Protective Surfacing Area (DIN EN 1176): 11.5 m x 11.5 m Protective Surfacing Area (ASTM 1487): 10.8 m x 10.8 m (35'-5" x 35'-5")

Minimum space required DIN EN 1176: 97.4 m<sup>2</sup> Minimum space required ASTM 1487: 86.7 m<sup>2</sup> (933.2 sf) Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Certificate according to DIN EN 1176:

4 pc. 2.9 m³ (102.4 ft³)

7 hours ø 0.1 m x 3.2 m (0'-4" x 10'-6")

180 kg (396.8 lbs) 3.6 m3 (127.1 ft3) Lifelong

No.: Z2 16 01 10256 246


**TÜV Product Service** 




Tel. +49.(0)30.41 47 24-0 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com Revision: March 2016 www.berliner-seilfabrik.com Page 1

# **Spaceball XL - Product Specification**





### **Technical Data.**

The following text can also be used for tenders.

#### **Tube framework:**

Frameworx-steel tubes, Ø 60.3 mm (2 3/8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

#### Nodes:

Frameworx-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

#### **Ropes:**


U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter Ø 16 mm (5/8")

#### Spacial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situ-replaceable rope strands (no special tools required)



Tel. +49.(0)30.41 47 24-0 Fax +49.(0)30.41 47 24-33



info@berliner-seilfabrik.com

www.berliner-seilfabrik.com

Revision: March 2016

Page 2