# **Spaceball M – Product Specification**



### Univers - Classics among rope playground equipment

Net structures offer hours of fun and adventure on several levels – climbing and swinging, up and down, horizontally and vertically – space on earth.

The original spatial nets: Born over 40 years ago as a play concept, continuously further developed in form and detail, still popular even after several generations.

## Spaceball M - at a glance.

**Product Family:** Univers Item Number: 90.100.041 Children's Age: Fall Height (DIN EN 1176): 1.49 m (4'-11") Length x Width x Height: (14'-5" x 14'-5" x 12'-0")

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

4.4 m x 4.4 m x 3.7 m

7.4 m x 7.4 m 8.1 m x 8.1 m (26'-5" x 26'-5")

40.8 m<sup>2</sup> 48.7 m<sup>2</sup> (524.2 sf) Number of Foundations: Concrete Volume C20/C25:

Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Certificate according to DIN EN 1176:

4 pc.

1.5 m<sup>3</sup> (53.0 ft<sup>3</sup>)

6 hours ø 0.1 m x 1.8 m (0'-4" x 5'-11")

130 kg (286.6 lbs) 2.7 m3 (95.3 ft3) Lifelong


No.: Z2 16 01 10256 246 **TÜV Product Service** 




Tel. +49.(0)30.41 47 24-0 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com Revision: March 2016 www.berliner-seilfabrik.com Page 1

# **Spaceball M – Product Specification**





#### **Technical Data.**

The following text can also be used for tenders.

#### **Tube framework:**

Frameworx-steel tubes, Ø 60.3 mm (2 3/8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

#### **Nodes:**

Frameworx-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

### Ropes:

U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter Ø 16 mm (5/8")

#### Spacial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situ-replaceable rope strands (no special tools required)





Tel. +49.(0)30.41 47 24-0 Fax +49.(0)30.41 47 24-33