# **Little Big Ben – Product Specification**



#### Little Big Ben

The jolly merry-go-round moves players around while squatting or standing. A combination of striking design and color together with the aim to encourage mobility, make Little Big Ben an attractive spinning island as well as a meeting point for all ages.

# URBAN DESIGN



#### Little Big Ben - at a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

**Playpoints 90.260.303** 

3+

0.75 m (2'-6") 1.3 m x 1.3 m x 0.8 m (4'-4" x 4'-4" x 2'-8")

5.4 m x 5.4 m 4.9 m x 4.9 m (16'-1" x 16'-1")

21.5 m<sup>2</sup> 18.8 m<sup>2</sup> (203 ft<sup>2</sup>) Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation:

Dimensions of largest part:

Weight of the heaviest part: Shipping Volume: Shipping Weight: Spare part guarantee:

Certificate according to DIN EN 1176:

1 pc. 0.3 m<sup>3</sup> (11 ft<sup>3</sup>)

2 2 hours

1.3 m x 1.3 m x 1.0 m (4'-4" x 4'-4" x 3'-4")

90 kg (199 lbs) 2.1 m³ (75 ft³) 100 kg (221 lbs)

Lifelong

No.: Z2 15 06 10256 233 TÜV Product Service

## **Technical Data.**

The following text can also be used for tenders.

### Turntable:

Stainless steel plate Ø 1230 mm (4'-1"), covered with HDPE panels, the cheeks are welded with stainless steel handrails Ø 60,3 mm (2 3/8")

#### Tubes:

Stainless steel tubes, Ø 60.3 mm (2 3/8")

#### Stand:

Stainless steel Picolino swivel stand with fully encapsulated bearing

#### **Nodes:**

Frameworx®-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; securely closed with durable EPDM-caps

# Covering:


Antiskid HDPE panels bolted on the turntable



Berliner Seilfabrik GmbH & Co. Lengeder Straße 2/4 D-13407 Berlin

Tel. +49.(0)30.41 47 24-0 Fax +49.(0)30.41 47 24-33







info@berliner-seilfabrik.com www.berliner-seilfabrik.com

Revision: May 2016 Page 1